

**CENTER 300/301/302/303 Thermometer (K Type, K J Type)**



**FEATURES**

- Timer Function (300, 302)
- Dual Input (301, 303)
- Dual Display (301, 303)
- PC Interface
- Auto Power Off
- Resolution 0.1°C, 0.1°F



- 300 K Type
- 301 K Type Dual Input
- 302 K J Type
- 303 K J Type Dual Input

**SPECIFICATIONS**

Range	K type: -200 ~ 1370°C, -328 ~ 2498°F (300 ~ 303) J type: -200 ~ 760°C, -328 ~ 1400°F (302 ~ 303)
Accuracy	±0.1%+0.7°C, ±0.1%+1.4°F
Resolution	0.1°C, 0.1°F
Operation Temp.	0°C ~ 50°C (<80%RH)
Storage temp.	-20°C ~ 60°C (<70%RH)
Battery	9V Battery
Dimensions	184 x 64 x 30 mm
Weight	Approx. 210g.

**STANDARD ACCESSORIES**

MODEL	Battery	Manual	Carrying case	K-Type bead sensor	RS-232 cable	Software
CENTER 300	•	•	•	TP-K01 x 1 PC	Option	Option
CENTER 301	•	•	•	TP-K01 x 2 PCS		
CENTER 302	•	•	•	TP-K01 x 1 PC		
CENTER 303	•	•	•	TP-K01 x 2 PCS		

**CENTER 307/308 Thermometer (K Type, Compact Size, Low Cost)**



**FEATURES**

- Mini Size
- Dual Input (308)
- Dual Display (308)
- Auto Power Off
- Resolution 0.1°C, 0.1°F



- 307 K Type
- 308 K Type Dual Input

**SPECIFICATIONS**

Range	-200 ~ 1370°C, -328 ~ 2498°F
Accuracy	±0.3%+1°C, ±0.3%+2°F
Resolution	0.1°C, 0.1°F
Operation Temp.	0°C ~ 40°C (<80%RH)
Storage temp.	-10°C ~ 60°C (<70%RH)
Battery	9V Battery
Dimensions	164 x 54 x 34 mm
Weight	Approx. 200g.

**STANDARD ACCESSORIES**

MODEL	Battery	Manual	K-Type bead sensor
CENTER 307	•	•	TP-K01 x 1 PC
CENTER 308	•	•	TP-K01 x 2 PCS

**CENTER 304 Thermometer (K Type, Four Channels Input)**



**FEATURES**

- Auto Power Off
- Four Channel Input
- Four Channel Display
- Wide Measuring Range
- PC Interface
- Resolution 0.1°C, 0.1°F



**SPECIFICATIONS**

Range	K Type:-200 ~ 1370°C, -328 ~ 2498°F
Accuracy	±0.3%+1°C, ±0.3%+2°F
Resolution	0.1°C, 0.1°F
Input Protection	60V DC or 24 Vrms AC Maximum
Operation Temp.	0°C ~ 50°C (<80%RH)
Storage temp.	-20°C ~ 60°C (<70%RH)
Battery	9V Battery
Dimensions	184 x 64 x 30 mm
Weight	Approx. 220g.

**STANDARD ACCESSORIES**

MODEL	Battery	Manual	Carrying case	K-Type bead sensor	RS-232 cable	Software
CENTER 304	•	•	•	TP-K01 x 2 PCS	Option	Option

RS-232 cable for PC interface (option)



LED Back Light