

**CENTER 310/311 Humidity Temperature Meter (Dual Input, PC Interface)****• FEATURES**

- Dual Input (311)
- Triple Display
- PC Interface
- Timer Function (310)
- REL Function (311)
- Auto Power Off
- Hold Function
- Max/Min Function
- Resolution 0.1°C, 0.1°F, 0.1%RH


 310 Single Input  
 311 Dual Input
**SPECIFICATIONS**

Range & Accuracy	Temperature : -20~60°C..±0.7°C -4~140°F..±1.4°F
	(K-Type) : -200~1370°C..±0.3%rdg + 1°C -328~2498°F..±0.3%rdg + 2°F
Humidity	0~100%RH..±2.5%RH
Input Protection	60V DC or 24Vrms AC Maximum
Battery	9V battery
Dimensions	Meter : 186 x 64 x 30mm Probe : 190 (L) x 15 (Dia) mm
Weight	Approx. 320g

**CENTER 313/314 Humidity Temperature Meter (Dual Input, Datalogger, PC Interface)****• FEATURES**

- Dual Input (314)
- Triple Display (314)
- PC Interface
- 16,000 Records Data Logger Per Channel
- Auto Power Off
- Clock Function
- Hold Function
- Max/Min Function
- Resolution 0.1°C, 0.1°F, 0.1%RH


 313 Single Input  
 314 Dual Input
**SPECIFICATIONS**

Range & Accuracy	Temperature : -20~60°C..±0.7°C -4~140°F..±1.4°F
	(K-Type) : -200~1370°C..±0.3%rdg + 1°C -328~2498°F..±0.3%rdg + 2°F
Humidity	0~100%RH..±2.5%RH
Input Protection	60V DC or 24Vrms AC Maximum
Battery	9V battery
Dimensions	Meter : 186 x 64 x 30mm Probe : 190 (L) x 15 (Dia) mm
Weight	Approx. 320g

**CENTER 315 Compact Size Humidity Temperature Meter****• FEATURES**

- Fast Response Time
- Auto Shut Off For Battery Saving
- REL Function
- Max/Min Function
- Dual Displays:  
Primary Display For Humidity;  
Secondary Displays For Temperature

**SPECIFICATIONS**

Range	Temperature : -20~60°C; -4~140°F; Humidity: 0~100%RH
Accuracy	±0.8°C , 1.6°F ±3%RH
Resolution	0.1°C; 0.1°F; 0.1%RH
Operation Temp	0°C~40°C (<80%RH)
Storage Temp	-10°C~60°C (<70%RH)
Battery	9V battery
Dimensions	240 x 54 x 34mm
Weight	Approx. 220g