

**CENTER 370 RTD Thermometer (Water Proof)**

● **FEATURES**

- IP 67 Water Proof Housing to work for almost all Kinds of Environments
- PT Temperature Sensor for less Environmental Dependent Reading
- Adapt for PT100, PT500 and PT1000 Sensors with  $\alpha$  Value of 3850
- MAX/MIN/Avg. Function
- LCD Back Light
- °C, °F Scale selectable and 0.1°C, 0.1°F Resolution
- 3 Sectors Battery Life Indicator



**SPECIFICATIONS**

Measurement Range	-100 ~ 300°C; -148 ~ 572°F
Measurement Accuracy	±0.1%rdg ±0.4°C
Resolution	0.1°C; 0.1°F
Sampling Rate	2 times/sec.
Water Resistance	IP67 (EN60529:1991)
Battery	1.5V, size AAA battery x3
Dimensions	150 x 66 x 31mm
Weight	Approx. 175g.
Sensor Type	Platinum temperature-measurement resistor (PT100/4 line type)



Within PT100 Probe (TP-R01 x 1pc.)

**STANDARD ACCESSORIES**

PT100 Probe (Class A) , Battery , Instruction Manual.

**FUNCTION TABLE**

MODEL	CENTER 370	CENTER 372
°C, °F Selectable	•	•
Dual Display	•	•
Dual Input Channels		•
LCD Back Light	•	•
Auto Power Off	•	•

**CENTER 372 RTD Thermometer (Water Proof/Data Input)**

● **FEATURES**

- IP 67 Water Proof Housing to work for almost all Kinds of Environments
- PT Temperature Sensor for less Environmental Dependent Reading
- PT100 Sensor with  $\alpha$  Value of 3850/3926/3916 RTD Standard
- MAX/MIN/Avg. Function
- LCD Back Light
- °C, °F Scale selectable and 0.1°C, 0.1°F Resolution
- 3 Sectors Battery Life Indicator
- Dual Input Channels



TP-R01

Within PT100 Probe (TP-R01 x 2pcs.)